

WHAT IS CLAIMED IS:

1. A camera comprising:

detection means for detecting connection with a printer; and

5 shift means for shifting to a print mode in response to the detection of the printer by said detection means.

2. A camera comprising:

10 detection means for detecting connection with a printer; and

shift means for shifting to a print mode in case of detection of a printer by said detection means in a reproduction mode.

15

3. A camera according to claim 2, further comprising display means for displaying, at the shift to said print mode, a mark indicating the shift to the print mode.

20

4. A camera according to claim 2, further comprising means for causing display of a style confirming image in response to the depression of a predetermined button after the shift to said print  
25 mode and causing printing of the image in response to the depression of a predetermined button.

1003115 020403

5. A camera according to claim 4, further comprising means for executing a change in the style after the display of the style confirming image.

5 6. A camera according to claim 2, further comprising conversion means for converting an image pickup signal from image pickup means into an image signal, recording means for recording, on a recording element, the image signal converted by said  
10 conversion means, and display means for displaying an image based on the image signal recorded on said recording element.

7. A printer comprising:  
15 identification means for identifying whether there is connected a cable for connection with a device serving as a host or a cable for connection with a device serving as a function; and  
setting means for setting as a host or a  
20 function according to the result of identification by said identification means.

8. A printer according to claim 7, further comprising print means, in case of setting as said  
25 host, for requesting print data to the connected device and executing printing based on the print data received from the device, and, in case of setting as

1006155-020402

said function, for receiving a print request from the connected device, informing the device of a print enabled state and executing printing based on the print data received from the device.

5

9. A printer according to claim 7, wherein said setting means executes setting as the host in case the connected device is a camera and setting as the function in case the connected device is a computer.

10

10. A printer according to claim 7, wherein, in case of setting as said host, said print means receives a print request from the connected device, requests print data to the device and executes printing based on the print data received from the device.

15

11. A control method for a camera, comprising:

20

a detection step of detecting connection with a printer; and

a shift step of shifting to a print mode in response to the detection of the printer by said detection step.

25

12. A control method for a camera,

comprising:

a detection step of detecting connection with a printer; and

a shift step of shifting to a print mode in  
5 case of detection of a printer by said detection step in a reproduction mode.

13. A control method according to claim 12,  
further comprising a display step of displaying, at  
10 the shift to said print mode, a mark indicating the shift to the print mode.

14. A control method according to claim 12,  
further comprising a step of causing display of a  
15 print style in response to a first instruction after the shift to said print mode and causing printing of the displayed image in response to a second instruction.

15. A control method according to claim 14,  
further comprising a step of executing a change in  
20 the print style after the display of the print style.

16. A control method according to claim 14,  
25 wherein said first and second instructions are instructions based on the depression of a same button.

1006455.00002

17. A control method for a printer,  
comprising:

an identification step of identifying whether  
there is connected a cable for connection with a  
5 device serving as a host or a cable for connection  
with a device serving as a function; and  
a setting step of setting as a host or a  
function according to the result of identification by  
said identification step.

10

18. A control method according to claim 17,  
further comprising a print step, in case of setting  
as said host, of requesting print data to the  
connected device and executing printing based on the  
15 print data received from the device, and, in case of  
setting as said function, of receiving a print  
request from the connected device, informing the  
device of a print enabled state and executing  
printing based on the print data received from the  
20 device.

19. A control method according to claim 17,  
wherein said setting step executes setting as the  
host in case the connected device is a camera and  
25 setting as the function in case the connected device  
is a computer.

20140220 15:54:30

20. A control method according to claim 17,  
wherein, in case of setting as said host, said print  
step receives a print request from the connected  
device, requests print data to the device and  
5 executes printing based on the print data received  
from the device.

21. A memory medium storing a control program  
for a camera, the control program comprising:  
10 a detection step of detecting connection with a  
printer; and  
a shift step of shifting to a print mode in  
response to the detection of the printer by said  
detection step.

15 22. A memory medium storing a control program  
for a camera, the control program comprising:  
a detection step of detecting connection with a  
printer; and  
20 a shift step of shifting to a print mode in  
case of detection of a printer by said detection step  
in a reproduction mode.

23. A memory medium according to claim 22,  
25 wherein the control program further comprises a  
display step of displaying, at the shift to said  
print mode, a mark indicating the shift to the print

10061155 020402

mode.

24. A memory medium according to claim 22,  
the control program further comprises a step of  
5 causing display of a print style in response to a  
first instruction after the shift to said print mode  
and causing printing of the displayed image in  
response to a second instruction.

10 25. A memory medium according to claim 24,  
wherein the control program further comprises a step  
of executing a change in the print style after the  
display of the print style.

15 26. A memory medium according to claim 24,  
wherein said first and second instructions are  
instructions based on the depression of a same button.

20 27. A memory medium storing a control program  
for a printer, the control program comprising:

an identification step of identifying whether  
there is connected a cable for connection with a  
device serving as a host or a cable for connection  
with a device serving as a function; and  
25 a setting step of setting as a host or a  
function according to the result of identification by  
said identification step.

28. A memory medium according to claim 17,  
wherein the control program further comprises a print  
step, in case of setting as said host, of requesting  
print data to the connected device and executing  
5 printing based on the print data received from the  
device, and, in case of setting as said function, of  
receiving a print request from the connected device,  
informing the device of a print enabled state and  
executing printing based on the print data received  
10 from the device.

29. A memory medium according to claim 27,  
wherein said setting step executes setting as the  
host in case the connected device is a camera and  
15 setting as the function in case the connected device  
is a computer.

30. A memory medium according to claim 27,  
wherein, in case of setting as said host, said print  
20 step receives a print request from the connected  
device, requests print data to the device and  
executes printing based on the print data received  
from the device.

25 31. A control program for a camera,  
comprising:

a detection step of detecting connection with a

printer; and

a shift step of shifting to a print mode in response to the detection of the printer by said detection step.

5

32. A control program for a camera, comprising:

a detection step of detecting connection with a printer; and

10 a shift step of shifting to a print mode in case of detection of a printer by said detection step in a reproduction mode.

33. A control program according to claim 32,  
15 further comprising a display step of displaying, at the shift to said print mode, a mark indicating the shift to the print mode.

34. A control program according to claim 32,  
20 further comprising a step of causing display of a print style in response to a first instruction after the shift to said print mode and causing printing of the displayed image in response to a second instruction.

25

35. A control program according to claim 14, further comprising a step of executing a change in

the print style after the display of the print style.

36. A control program according to claim 34,  
wherein said first and second instructions are  
5 instructions based on the depression of a same button.

37. A control program for a printer,  
comprising:

an identification step of identifying whether  
10 there is connected a cable for connection with a  
device serving as a host or a cable for connection  
with a device serving as a function; and

a setting step of setting as a host or a  
function according to the result of identification by  
15 said identification step.

38. A control program according to claim 37,  
further comprising a print step, in case of setting  
as said host, of requesting print data to the  
20 connected device and executing printing based on the  
print data received from the device, and, in case of  
setting as said function, of receiving a print  
request from the connected device, informing the  
device of a print enabled state and executing  
25 printing based on the print data received from the  
device.

39. A control program according to claim 37,  
wherein said setting step executes setting as the  
host in case the connected device is a camera and  
setting as the function in case the connected device  
5 is a computer.

40. A control program according to claim 37,  
wherein, in case of setting as said host, said print  
step receives a print request from the connected  
10 device, requests print data to the device and  
executes printing based on the print data received  
from the device.

41. A print system comprising:  
15 a camera including detection means for  
detecting connection with a printer, and shift means  
for shifting to a print mode in response to the  
detection of the printer by said detection means; and  
a printer including identification means for  
20 identifying whether there is connected a cable for  
connection with a device serving as a host or a cable  
for connection with a device serving as a function,  
and setting means for setting as a host or a function  
according to the result of identification by said  
25 identification means.

1006153.020402